

VERSE™ 3" LED

REMODEL FIXED AND WALL WASH DOWNLIGHTS

The VERSE 3" LED Remodel Fixed and Wall Wash Downlights offer a cost-effective alternative for residential, multifamily, and hospitality applications without sacrificing aesthetics or quality. VERSE is IC-rated and provides a minimal profile without the need for a large housing. The LED subassembly and driver ship integrated with the housing which eliminates a second wiring step after the ceiling is installed.

- 951 lumens
- 2700K and 3000K; 90+ CRI
- Easy installation
- Light source is integrated as part of the housing
- One housing for round and square trim options
- 3.8" tall housing fits into shallow plenums
- Collar notches assist in the alignment of multiple housings
- IC-rated, airtight, wet-rated
- Patent pending



FIXED



WALL WASH

SPECIFICATIONS

	REMODEL FIXED		REMODEL WALL WASH	
	2700K	3000K	2700K	3000K
DELIVERED LUMENS	903	951	713	750
WATTS	9W			
EFFICACY	100	106	73	77
CRI	90+			
COLOR CONSISTENCY	3-step			
VOLTAGE	120V			
DIMMING ¹	Reverse phase, Forward phase, and TRIAC dimming down to 2% to 4% with several dimmers			
POWER SUPPLY	Constant current driver with +.9 power factor and +80% efficiency			
OPTICS	Diffused lens provides 70° beam spread		Asymmetric Wall Wash	
CEILING APPEARANCE	Flanged up to 3/4" ceiling thickness			
CEILING APERTURE	4" ceiling cutout 2" aperture			
HOUSING	IC Airtight; suitable up to R60 spray foam insulation			
CONSTRUCTION	Housing: Galvanized Steel Trims: Die-Cast Aluminum			
FINISH	White (field paintable)			
GENERAL LISTINGS	ETL listed. Wet-rated.			
CALIFORNIA TITLE 24	Registered CEC Appliance Database. Can be used to comply with CEC 2019 Title 24 Part 6 (JA8-2016, JA8-2019).			
L70	50,000 hours min			
WARRANTY ²	5 years			

Ordering grids available on page 2.

¹See visualcomfort.com for dimmer compatibility.

²Visit visualcomfort.com for specific warranty limitations and details.



©2023 Visual Comfort & Co. All rights reserved. The Visual Comfort & Co. logo is a registered trademark.
Visual Comfort & Co. reserves the right to change specifications for product improvements without notification.

UPDATED 12/19/22

VERSE™ 3" LED

REMODEL FIXED AND WALL WASH DOWNLIGHTS

ORDERING INFORMATION

HOUSING

ITEM NUMBER	DESCRIPTION
V3RR27	VERSE 3" REMODEL HOUSING 2700K
V3RR30	VERSE 3" REMODEL HOUSING 3000K

Trims are required and must be ordered separately.
All housings are IC-rated, airtight and wet-rated.
All modules are 120V.


TRIM

ITEM NUMBER	DESCRIPTION
V3RDWH	VERSE 3" ROUND FIXED
V3RWWH	VERSE 3" ROUND WALL WASH
V3SDWH	VERSE 3" SQUARE FIXED
V3SWWH	VERSE 3" SQUARE WALL WASH

All trims are flanged white.


TRIMS

FIXED




SQUARE FLANGED


WALL WASH



SQUARE FLANGED



ROUND FLANGED



ROUND FLANGED

HOUSING



IC AIRTIGHT

VERSE™ 3" LED

REMODEL FIXED AND WALL WASH DOWNLIGHTS

PHOTOMETRICS

Description: 3" LED Downlight
3000K

Model: Verse 9W Fixed

Input Power (Watts): 8.85

Input Power Factor: 0.99

Absolute Luminous Flux (Lumens): 936

Lumen Efficacy (Lumens per Watt): 105.7

Description: 3" LED Downlight
3000K

Model: Verse 9W Wall Wash

Input Power (Watts): 8.83





Input Power Factor: 0.99

Absolute Luminous Flux (Lumens): 660

Lumen Efficacy (Lumens per Watt): 74.8

ANGLE	0°	45°	90°
0°	509	509	509
5°	505	507	507
10°	501	503	501
15°	492	491	487
20°	475	470	465
25°	449	441	433
30°	413	402	394
35°	367	355	346
40°	312	300	291
45°	255	242	233
50°	190	177	168
55°	126	117	111
60°	79	72	69
65°	46	42	41
70°	25	22	22
75°	12	10	10
80°	5	4	4
85°	2	2	2
90°	0	0	0

ANGLE	0°	45°	90°
0°	222	222	222
5°	201	204	220
10°	184	189	213
15°	178	179	205
20°	178	172	192
25°	178	171	178
30°	174	169	163
35°	166	162	148
40°	153	151	133
45°	135	135	119
50°	115	118	104
55°	91	97	89
60°	69	76	71
65°	47	54	53
70°	27	33	35
75°	13	15	20
80°	6	5	9
85°	3	2	1
90°	0	0	0



VERSE™ 3" LED

REMODEL FIXED AND WALL WASH DOWNLIGHTS

PROJECT INFORMATION

JOB NAME AND INFORMATION

FIXTURE TYPE AND QUANTITY

NOTES
